



JOC306X Series

Rev.A.1.1

The JOC306X series combine an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon zero-cross photo triac in a plastic DIP6 package with different lead forming options. The products are widely used in solenoid/valve controls, lighting controls, motor controls, temperature controls, static AC power switches, solid state relays, interfacing microprocessors up to 265 VAC peripherals.

High isolation 5000 VRMS

DC input with zero-cross photo triac output

Operating temperature range -55 °C to 125 °C

Input: 0-10V, 0-5V, 0-1.5V

HBM: 1000V, 1000V, 1000V

CQC approved

VDE approved

UL approved

(Temperature=25°C)

Parameter		Symbol	Value	Unit
Input	Forward Current	I _F	60	mA
	Reverse Voltage	V _R	6	V
	Junction Temperature	T _j	125	
	Input Power Dissipation	P _I	100	mW
	Power Dissipation Derating (T _a 25 °C)	P _D /	-1.33	mW/
Output	Off-state Output Terminal Voltage	V _{OFF}	600	V
	Peak On-state Current (100µs pulse, 120 pps)	I _{TP}	2	A
	On-state RMS Current	I _{T(RMS)}	100	Peak mA

	Power Dissipation Derating ($T_a = 25^\circ\text{C}$)	$P_D/$	-3.33	mW/
Total Power Dissipation		P_{tot}	350	mW
Isolation Voltage		V_{iso}	5000	Vrms
Operating Temperature		T_{opr}	-55~100	
Storage Temperature		T_{stg}	-55~125	
Soldering Temperature		T_{sol}	260	

:AC for 1minute, R.H.=40~60%

:For 10 seconds


(Temperature=25°C)

Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit	
Input	Forward Voltage	V_F	$I_F=10\text{mA}$	-	1.27	2.2	V	
	Reverse Current	I_R	$V_R=6\text{V}$	-	-	1	μA	
	Input Capacitance	C_{in}	$V=0, f=1\text{kHz}$	-	10	-	pF	
Output	Peak Off-state Current, Either Direction	I_{OFF}	$V_{OFF}=600\text{V}, I_F=0$	-	-	100	nA	
	Peak On-state Voltage, Either Direction	V_{TM}	$I_{TM}=100\text{mA}$	-	1.7	2.5	V	
	Critical Rate of Rise of Off-state voltage	dV/dt	$V_{PEAK}=600\text{V}, I_F=0$	1000	-	-	V/ μs	
Transfer Characteristics	LED Trigger Current	JOC3061	Terminal Voltage=3V $I_{TM}=100\text{mA}$	-	-	15	mA	
		JOC3062		-	-	10		
		JOC3063		-	-	5		
	Holding Current		I_H	$I_{TM}=2\text{mA}, I_F=\text{Rated } I_{FT}$	-	250	-	μA
	Isolation Resistance		R_{ISO}	DC500V 40~60%R.H.	10^{12}	10^{14}	-	
	Floating Capacitance		C_{IO}	$V=0, f=1\text{MHz}$	-	10	-	pF
	Response Time		t_{on}	$V_D=6\text{V}, R_L=100\Omega, I_F=20\text{mA}$	-	15	50	μs
Inhibit Voltage		V_{IH}	$I_F=\text{Rated } I_{FT}$	-	-	20	V	

Zero-crossing Characteristics

Leakage in Inhibited

Stand-off Voltage V_{OFF} (2) T_j 10.56 0 0 10.56 293.76 108.12 T_m ($^\circ\text{C}$) T_j EMC /P <<MCID 164 >>BD



JOC : Company Abbr.
306X : Part Number & Rank
V : VDE Option
Y : Fiscal Year
A : Manufacturing Code
WW : Work Week


FIG.12: Test Circuits of Turn On Time

FIG.13: Waveforms of Turn On Time


Fig.14: Test Circuits of dV/dt

Fig.15: Waveforms of dV/dt


Option S Type:




Option SLM Type: Dimensions Millimeters Inches Ref. Min. Typ. Max. Min. Typ. Max.




Option SL






Option SLM



Standard DIP







Soldering Temperature	360± 5

Document Revision History

Date	Revision	Changes
Apr.2, 2025	A.1.0	Last update
Nov.5, 2025	A.1.1	Add S&SLM package

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which