



JOCMAB1C-D5P/S Series


Rev.A.1.0

DESCRIPTION:

The products are 5-pin optical relays. The device combines an AlGaAs infrared emitting diode input stage optically coupled to a high-voltage output detector circuit. The detector consists of a high-speed photovoltaic diode array and driver circuitry to switch on/off two discrete 1800V high voltage MOSFETs. The relay action with a minimum input current of 5mA through the input LED. The products are widely used in accumulation, automotive battery management system, automobile battery and power system insulation testing, industrial controls and EMR/reed relay replacement.

MAIN FEATURES:

- High isolation 5000 Vrms
- Single channel normally on Single-Pole-Single-Throw Relay
- Operating temperature range -40°C to 125°C
- REACH & RoHS compliance
- HBM: H3A; MM: M4; CDM: C3
- CQC approved
- VDE approved
- UL approved



ABSOLUTE MAXIMUM RATINGS (Temperature=25°C)

Parameter		Symbol	Value	Unit
Input	Forward Current	I_F	50	mA
	Peak Forward Current	I_{FP}	1	A
	Reverse Voltage	V_R	6	V
	Power Dissipation	P_D	75	mW
Output	Switching Voltage	V_O	1800	V
	Continuous Load Current	I_O	10	mA
	Power Dissipation	P_C	360	mW
Operating Temperature		T_{opr}	-40~125	
Junction Temperature		T_j	135	
Storage Temperature		T_{stg}	-55~125	



Total Power Dissipation	P_{tot}	450	mW
Isolation Voltage	V_{iso}	5000	Vrms
Soldering Temperature	T_{sol}	260	

NOTE1. 100μs pulse, 100Hz frequency

NOTE2 AC for 1minute, R.H.=40~60%

ELECTRICAL CHARACTERISTICS (Temperature=25°C)


Parameter		Symbol	Condition	Min.	Typ.	Max.	Unit
Input	Forward Voltage	V_F	$I_F=10mA$	-	1.2	1.5	V
	Reverse Current	I_R	$V_R=6V$	-	-	1	μA
	Terminal Capacitance	C_t	$V=0, f=1MHz$	-	30	-	pF
	Reset Current	$I_{F(OFF)}$	$I_O=I_{O(MAX)}$	0.4	-	-	mA
Output	Off-state Leakage Current	I_{OFF}	$V_O=1800V$	-	-	10	μA
	ON Resistance	R_{ON}	$I_O=I_{O(MAX)}, I_F=5mA$	-	200	500	
Transfer Characteristics	LED Trigger Current	I_{FT}	$I_O=I_{O(MAX)}$	-	-	3	mA
	Floating Capacitance	C_{IO}	$V=0, f=1MHz$	-	3	-	pF
	Isolation Resistance	R_{ISO}	DC500V 40~60%R.H.	10^{12}	-	-	
	Turn On Time	t_{on}	$I_O=10mA, I_F=5mA$	-	0.2	1	ms
	Turn Off Time	t_{off}	$I_O=10mA, I_F=5mA$	-	0.1	0.2	ms

JOCMAB1C

JOCMAB1C

Package Dimension (Unit: mm)

Standard DIP Type:



Ref.	Dimensions					
	Millimeters			Inches		
	Min.	Typ.	Max.	Min.	Typ.	Max.
A						
B						
C						
D						
E						
F						
G						
H						
I						
J						



RECOMMENDED SOLDER MASK (Dimensions in mm unless ot &





CARRIER TAPE SPECIFICATIONS (Dimensions in mm unless otherwise stated)


Ref.	Dimensions	
	Millimeters	Inches
Min	Min.Mz	Min.Mzm



REFLOW INFORMATION



WAVE SOLDERING



HAND SOLDERING BY SOLDERING IRON


Soldering Temperature	360±5
Soldering Time	3s max.

Note:

1. Reflow soldering is recommended at the temperatures and times shown, no more than three times.
2. Avoid direct contact between the epoxy body and any tools or surfaces exceeding its maximum storage temperature.
3. Application of pressure on the epoxy body is prohibited at elevated temperatures. In specific scenarios, any applied force must not exceed 2.5N.
4. Ensure the component has cooled to ambient temperature before proceeding with any subsequent manufacturing steps.
5. The component has a shelf life of one year when stored under standard conditions.
6. Recommend storage Temp.: 0~40°C;
Recommend storage humidity: <60%;
MSL level: MSL 1

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.

Copyright © 2026 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.