




### 59 o/k Lt u L \ b

The products are 5-pin solid-state relay opto-couplers. The device combines an AlGaAs infrared emitting diode as the emitter which is optically coupled to a monolithic silicon random-phase photo triac to drive a power triac in a plastic DIP5 package with different lead form options. The products are widely used in solenoid/valve controls, lighting controls, motor controls, temperature controls, static AC power switches, solid state relays, interfacing microprocessors to 265V peripherals.



### a ° Lb C9 ° u y k 9 o


- Isolation: 5000 Vrms
- DC input / triac output
- Operating temperature range: -40 °C to 110 °C
- REACT / RoS compliance
- BM: 3B / MM: M4 / CDM: C3
- CEC approved
- VDE approved
- UL approved

### ° .o \ O y u 9 a ° CELaya kfi Temperature 125 °C

Parameter		Symbol	Value	Unit
Input	Forward Current	$I_F$	50	mA
	Peak Forward Current	$I_{FP}$	1	A
	Reverse Voltage	$V_R$	6	V
	Power Dissipation	$P_D$	75	mW
Output	Repetitive peak on-state voltage	$V_{DRM}$	600	V
	Repetitive peak reverse voltage	$V_{RRM}$	600	V
	Critical rate of rise of state current	$di/dt$	100	A/ s
	On-state RMS Current @ 80°C	$I_{T(RMS)}$	7.5	A
	1RQ UHSHWJLWISYHDNRQ VWDWH FXUUHQW IXOQV\FOH W <sup>760</sup> MXQFWLRQ WRFDVH \$ & 5WK MF			




\ k 59 k LbD LbC \ ka ° uL \ b



t v	
\	v
5Lt	y u
o a5	y k

a ° k MLbD



/

/

FIG.1: Max. Allowable LED Forward Current vs. Ambient Temperature




FIG.2: On-state Terminal Current vs. Ambient Temperature




FIG.7: On-state characteristics




FIG.8: Normalized  $\theta_{JA}$  [ Current vs. Ambient Temperature






FIG.9: Turn On Time vs. Forward Current





t 5 y


Standard DIP Type:



Dimensions  
Millimeters      Inchio



Option SMD

Option SMD



Standard DIP


Standard DIP







‡ ° †9 o \ O59 k LbD



I ° b5 o \ O59 k LbD . ' o \ O59 k LbD L k \ b	
Solderin [ Temperature	360w5
Solderin [ Time	3s max.



**Note:**

1. Re Z lo k solderin [ is recommended at t \ e temperatures and times s \ o k n, no more t \ ree times.
2. Avoid direct contact bet k e e n \ e epoxy body and any tools osur Z aces exceedin [ its maximum stora [ e temperature.
3. Applicati o Z p s s u r e on t \ e epoxy body s s o n                    va [ A