


urpose
nction in
on motor
ight
25-8H
e turn-off
00-4-5
t.



Symbol	Value	Unit
T _{stg}	-40-150	
T _j	-40-125	

V _{RRM}	800	V
------------------	-----	---

I_R

Peak pulse voltage ($T_j=25$; non-repetitive, off-state; FIG.7)	V_{pp}	3.5	kV
--	----------	-----	----

ELECTRICAL CHARACTERISTICS ($T_j=25$ unless otherwise specified)

Symbol	Test Condition	Quadrant	Value		Unit
I_{GT}	$V_D=12V$ $R_L=33\Omega$	- -	MAX.	25	mA
V_{GT}		- -	MAX.	1	V
V_{GD}	$V_D=V_{DRM}$ $T_j=125$ $R_L=3.3k\Omega$	- -	MIN.	0.2	V
I_L	$I_G=1.2I_{GT}$	-	MAX.	40	mA
				60	
I_H	$I_T=100mA$		MAX.	40	mA
dV/dt	$V_D=540V$ Gate Open $T_j=125$		MIN.	2500	V/ μs
(dI/dt) c	(dV/dt) $c=20V/\mu s$, $T_j=125$		MIN.	8	A

ORDERING INFORMATION

AC	J	T	6	25	-8	H
AC switch		Triacs				H:TO-251
JieJie Microelectronics Co., Ltd.		$I_{T(RMS)}:6A$				
		25: $I_{GT1-3} \leq 25mA$			8: $V_{DRM} / V_{RRM} \geq 800V$	

MARKING



	XXX XXX Year ——— Production Code Month ——— Code
---	--

FIG.7 Test circuit for inductive and resistive loads to IEC-61000-4-5 standards



LEAD FORMING AND SOLDERING

ORDERING INFORMATION

Order code	Voltage V _{DRM} /V _{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
ACJT625-8H	800	25	TO-251	80	Tube

Document Revision History

Date	Revision	Changes
------	----------	---------

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd.
Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.