




JCT151F-500R 12A SCR

Rev.A.1.1

DESCRIPTION:

With high ability to withstand the shock loading of large current, JCT151F-500R of silicon controlled rectifiers provides high dV/dt rate with strong resistance to




I _{GM}	4	A
P _{G(AV)}	1	W
P _{GM}	10	W
V _{pp}	0.7	kV

(Unless otherwise specified)

	Value			Unit
	MIN.	TYP.	MAX.	
	-	-	15	mA
	-	-	1	V
	0.2	-	-	V
	-	-	40	mA
	-	-	30	mA
	1000	-	-	V/μs
	-	3	-	μs
	-	50	-	

	Value(MAX.)	Unit
	1.6	V
	1.6	mA

ORDERING INFORMATION



JCT151F-500R


ORDERING INFORMATION

Order code	Voltage V_{DRM}/V_{RRM} (V)	IGT(mA)	Package	Base qty. (pcs)	Delivery mode
JCT151F-500R	500	15	TO-220F(Ins)	50	Tube

Document Revision History

Date	Revision	Changes
May 17, 2023	A.1.0	Last update
Sept.28, 2025	A.1.1	Revise PACKAGE MECHANICAL DATA

Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document supersedes and replaces all information previously supplied.

 is a registered trademark of Jiangsu JieJie Microelectronics Co., Ltd. Copyright © 2025 Jiangsu JieJie Microelectronics Co., Ltd. All rights reserved.