




JCT612A 12A SCR

Rev.A.1.1

DESCRIPTION:

With high ability to withstand the shock loading of large current, JCT612A of silicon controlled rectifiers provides high dV/dt rate with strong resistance to electromagnetic interference. It is especially recommended for use on solid state relay, motorcycle, power charger, T-tools etc. From all three terminals to external heatsink, JCT612A provides a rated insulation voltage of 2500 V_{RMS}, complying with UL standards (File ref: E252906). Package TO-220A is RoHS compliant.



MAIN FEATURES

ABSOLUTE MAXIMUM RATINGS

Parameter	Symbol	Value	Unit
Storage junction temperature range	T _{stg}	-40-150	
Operating junction temperature range	T _j	-40-125	
Repetitive peak off-state voltage (T _j =25)	V _{DRM}	600	V
Repetitive peak reverse voltage (T _j =25)	V _{RRM}	600	V
Average on-state current (T _c ≤ 89)	I _{T(AV)}	7.6	A
RMS on-state current (T _c ≤ 89)	I _{T(RMS)}	12	A

48.92pt(16.4mm)7.62pt(24.4mm)10.16pt(31.0mm)1.6mm 71.16 161.4 254.64 31.-. <</MCID 48 >>BDC

JCT612A

ORDERING INFORMATION

<u>J</u>	<u>CT</u>	<u>6</u>	<u>12</u>	<u>A</u>
JieJie Microelectronics Co., Ltd.	SCRs	$6: V_{DRM} / V_{RRM} \geq 600V$	$I_{T(RMS)}: 12A$	A: TO-220A(Ins)

MARKING





	<table><tr><td></td><td><u>XXX</u></td><td><u>XXX</u></td><td></td></tr><tr><td>Year</td><td></td><td></td><td>Production</td></tr><tr><td>Month</td><td></td><td></td><td>Code</td></tr></table>		<u>XXX</u>	<u>XXX</u>		Year			Production	Month			Code
	<u>XXX</u>	<u>XXX</u>											
Year			Production										
Month			Code										

FIG.1: Maximum power dissipation versus RMS on-state current**FIG.2:** RMS on-state current versus case temperature

JCT612A

JieJie Microelectronics Co., Ltd.

PACKAGE MECHANICAL DATA



Information furnished in this document is believed to be accurate and reliable.

However, Jiangsu JieJie Microelectronics Co., Ltd. assumes no responsibility for the consequences of use without consideration for such information nor use beyond it.

Information mentioned in this document is subject to change without notice, apart from that when an agreement is signed, Jiangsu JieJie complies with the agreement.

Products and information in this document are for reference only. No part of this document may be reproduced or transmitted in any form or by any means electronic or mechanical, including photocopying, recording, or by any information storage and retrieval system, without permission in writing from Jiangsu JieJie Microelectronics Co., Ltd.