



- Half-bridge SCR configuration integrated in a single package
- With high thermal conductivity DBC as the Insulation
- Welding by vacuum welding technology, which provide high reliability

Applications

- Temperature control
- Light control system
- DC motor

Absolute Maximum Ratings (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)

Parameter	Conditions	Symbol	Values	Unit
Repetitive peak off-state voltage	$T_{vj} = 25^\circ\text{C}$	V_{DRM}	1800	V
Repetitive peak reverse voltage	$T_{vj} = 25^\circ\text{C}$	V_{RRM}	1800	V
Non-repetitive peak off-state voltage	$T_{vj} = 25^\circ\text{C}$	V_{DSM}	1900	V
Non-repetitive peak reverse voltage	$T_{vj} = 25^\circ\text{C}$	V_{RSM}	1900	V
Average forward current	$T_C = 85^\circ\text{C}$	$I_{T(AV)}$	250	A
Forward surge current	$t_P=10\text{ms } V_R=0.6V_{RRM}$	I_{TSM}	8300	A
I^2t value for fusing		I^2t	344450	A^2s
Critical rate of rise of on-state current	$I_G=2 \times I_{GT}$	di/dt	150	$\text{A}/\mu\text{s}$
RMS isolation voltage	A.C 50Hz(1s/1min)	V_{ISO}	3600/3000	V
Junction temperature range		T_J	-40 ~ +125	

Storage temperature




Electrical Characteristics (@ $T_C = 25^\circ\text{C}$ unless otherwise specified)


Parameter	Conditions	Symbol	Values			Unit
			Min.	Typ.	Max.	

Peak forward voltage $I_T =$

Circuit Diagram




Package Outlines (mm)



Package Outlines (mm)



Information furnished in this document is believed to be accurate and reliable. However, Jiangsu JieJie Semiconductor Co., Ltd assumes no responsibility for the consequences of use without consideration for such information nor use beyond it. This information in this document is subject to change without prior notice. Notwithstanding this, Jiangsu JieJie will fully comply with the terms outlined in a signed agreement. Products and information provided in this document have no infringement of patents. Jiangsu JieJie assumes no responsibility for any infringement of other rights of third parties which may result from the use of such products and information. This document is the initial release, dated 2 April 2026. This document supersedes and replaces all information previously supplied.

 is registered trademark of Jiangsu JieJie Semiconductor Co., Lt ©2026 Jiangsu JieJie Semiconductor Co., Ltd. All rights reserved.